


# CT Analyzer

Current transformer testing, calibration and assessment



# Analyze your current transformer (CT) with the push of a button

## How CT Analyzer works

- > Injects low test signals into secondary side of the CT
- > Determines the CT's equivalent circuit parameters
- > Identifies all relevant CT performance parameters
- > Displays all relevant parameters of the CT and its accuracy at different currents and burdens
- > Evaluates the CT according to the selected standard
- > Determines unknown CT nameplate parameters
- > Demagnetizes the CT after the test

## Range of measurements

- > Ratio and phase accuracy
- > Winding resistance
- > Excitation characteristics (knee points)
- > Composite error (ALF, ALFi, FS, FSi,  $V_p$ )
- > Burden impedance
- > Transient CT classes and parameters (TPS, TPX, TPY and TPZ type CTs)
- > Transient dimensioning factor (Ktd)
- > If missing/unknown: CT type, class, ratio, knee point, power factor, nominal burden, operating burden, primary and secondary winding resistance
- > Remanence and residual magnetism
- > Immediate good/bad evaluation



**SAFE**  
low test signals



## Additional features

### > Simulate different burdens and currents

Will a change in the burden influence the accuracy of the measured CT? You can simply have CT Analyzer recalculate results for different burdens and primary currents without measuring again.

### > Analyze the effect of CT saturation

You can export the measurement results to network simulation software such as RelaySimTest or NetSim in order to analyze the protective system behavior under the effect of CT saturation.

### > Measure VT ratio

You can perform ratio measurements of inductive voltage transformers (VTs).

### > Multimeter

You can use the integrated multimeter with AC/DC current and voltage source for manual tests, such as L, Z, R, ratio, polarity and burden.



**EASY**  
one-button-test



**PROVEN**  
users in more  
than 120 countries



# Current transformer testing from production to maintenance

## Testing along the production line

- > Test CTs before adding the insulation
- > Verify CTs at various production stages
- > Achieve a high degree of automation
- > Use a universal interface to control the CT Analyzer from your very own production line software
- > Easily integrate the CT Analyzer into your company network and ERP system
- > Maximize your throughput by minimizing testing time
- > Reliably operate the CT Analyzer 24/7

## Factory acceptance testing

- > Determine the performance of the CTs and evaluate it according to the desired standard (IEC, IEEE or local)
- > Create a CT Analyzer fingerprint measurement for further on-site comparison
- > Verify the CT design



TEST



ASS

designed, tested and calibrated by OMICRON



### Commissioning

- > Quickly and reliably commission any CT (all protection and metering classes)
- > Compare your results with factory measurements
- > Verify the connection and polarity of the secondary wiring along all of the connection points from the CT secondary terminals to the connected instrument, such as a relay or meter


### Maintenance

- > Verify the CT at (different) operating conditions
- > Recover unknown CT nameplate data
- > Verify correct wiring and connections
- > Compare your results with previous results
- > Create customized reports (digital or printed)
- > Analyze the cause of a protection failure based on the determined CT parameters
- > Evaluate protection system behavior under CT saturation using real CT data with network simulation software such as RelaySimTest or NetSim
- > Achieve stable and reliable results, even under harsh environmental conditions





**ESS**

**CALIBRATE**




# Advantages and disadvantages of different CT testing methods

Method	Primary nominal current injection	Primary current injection
Setup	<ul style="list-style-type: none"> <li>&gt; Reference transformers and measuring bridges</li> </ul>	<ul style="list-style-type: none"> <li>&gt; Test set for current supply and measurement</li> </ul>
Usage	<ul style="list-style-type: none"> <li>&gt; Used in factories, calibration laboratories and on-site mounted on a test truck</li> </ul>	<ul style="list-style-type: none"> <li>&gt; Used during commissioning if high accuracy is not required</li> </ul>
Principle	 <p>The diagram shows a transformer mounted on a truck. The primary winding is connected to a current source, and the secondary winding is connected to a measuring bridge. The primary current is labeled <math>I_P</math> and the secondary current is labeled <math>I_S</math>.</p>	 <p>The diagram shows a transformer with a current source and an ammeter connected to the primary winding. The primary current is labeled <math>I_P</math> and the secondary current is labeled <math>I_S</math>.</p>
Safety	<ul style="list-style-type: none"> <li>&gt; Performed with very high currents (nominal and overcurrent magnitudes)</li> </ul>	<ul style="list-style-type: none"> <li>&gt; Currents up to 1000 A</li> </ul>
Accuracy	<ul style="list-style-type: none"> <li>&gt; High accuracy</li> </ul>	<ul style="list-style-type: none"> <li>&gt; Insufficient for high-accuracy metering CTs</li> <li>&gt; Sensitive to transient distortion if line frequency test signals are being used</li> </ul>
Mobility	<ul style="list-style-type: none"> <li>&gt; ~ Two tons of equipment (test truck, high-current source, heavy cables, current box, ...)</li> </ul>	<ul style="list-style-type: none"> <li>&gt; ~ 30 kg / 66 lbs (without additional equipment such as a burden box)</li> </ul>
Handling	<ul style="list-style-type: none"> <li>&gt; The heavy equipment requires several people to set up and perform the test</li> </ul>	<ul style="list-style-type: none"> <li>&gt; Rewiring is required between single tests (for example, ratio, polarity, saturation, winding resistance)</li> <li>&gt; Results must be assessed manually</li> </ul>

## Secondary voltage injection

- > Test set for voltage output and measurement of voltage and current
- > Used during commissioning or maintenance if a simple check of the CT's integrity from the secondary side is sufficient




- > Voltages up to 2 kV or more
- > Insufficient for high-accuracy CTs
- > Sensitive to transient distortion if line frequency test signals are being used

> ~ 20 kg / 44 lbs

- > Test results must typically be evaluated manually
- > Special attention has to be given to high-voltage leads and connections

## Model-based testing

- > Test set for low test signal injection and CT modelling
- > Used in all stages of a CT's life



> Output voltages up to 120 V

> Suitable for all classes, including class 0.1

> ~ 8 kg / 17 lbs

- > One-button test
- > Automated assessment
- > Integrated report
- > Fast (< 1 min)

# Operating options for the CT Analyzer: standalone or from a laptop

You have 3 different options for the operation of your CT Analyzer

The different options offer different feature sets

## 1. Stand-alone operation via free-of-charge CT Analyzer firmware

- > Input of CT parameters
- > Measurement and analysis
- > Automated assessment
- > Front-panel display of wiring diagrams and step-by-step instructions



## 2. PC operation via free-of-charge standard CT Analyzer Suite

- > Input of CT parameters
- > Measurement and analysis
- > Automated assessment
- > Multi-colored wiring diagrams and step-by-step instructions via PC screen
- > Definition of assessment standards and limits
- > Guided test preparation
- > Detailed connection diagrams
- > Automatic generation and display of reports
- > Customization of the report templates
- > Improved multi-ratio CT testing performance

## 3. PC operation via CT Analyzer Suite with PC Software Upgrade Option

- > Input of CT parameters
- > Measurement and analysis
- > Automated assessment
- > Multi-colored wiring diagrams and step-by-step instructions via PC screen
- > Definition of assessment standards and limits
- > Guided test preparation
- > Detailed connection diagrams
- > Automatic generation and display of reports
- > Customization of the report templates
- > Improved multi-ratio CT testing performance
- > Multi-test view
- > Advanced reporting
- > Reporting template designer
- > Ratio accuracy assessment for all taps (for multi-ratio tests)
- > Results simulation / re-calculation without connected device



\* optionally available transport case

## Optionally available accessories

### CT SB2: Switch box for multi-tap CT testing

- > Automates your testing of multi-tap CTs
- > No need for rewiring
- > Measures CTs with up to six taps in one test run
- > Determines all of the transformer ratios of all winding combinations automatically
- > Separate connections for primary resistance measurement and for the measurement of the secondary burden
- > Automatically verifies the cabling before measuring
- > Use it separate from, or attached to, CT Analyzer



### CPOL3: Polarity and wiring checker

- > Verifies correct polarity along all of the different terminals from the CT's secondary wiring all the way to the relay, meter or other secondary device
- > The polarity is verified using a sawtooth signal injected by the CT Analyzer running QuickTest





### Multi-functional transport case

- > Heavy duty transport case on wheels
- > Protection from dust and water drops
- > Protection from mechanical damage
- > Suitable for unattended shipping
- > Convertible into a workbench
- > Extendable lid and pluggable end plates



### Trolley / Backpack

- > Small and lightweight backpack carrying option
- > Wheels, extendable handle and shoulder straps
- > Basic mechanical protection

# Technical specifications

## CT Analyzer



### Accuracy

Ratio 1 ... 2000	error 0.02 % (typical) / 0.05 % (guaranteed)
Ratio 2000 ... 5000	error 0.03 % (typical) / 0.1 % (guaranteed)
Ratio 5000 ... 10000	error 0.05 % (typical) / 0.2 % (guaranteed)

### Phase displacement

Resolution	0.01 min
Accuracy	1 min (typical) / 3 min (guaranteed)

### Winding resistance

Resolution	1 mΩ
Accuracy	0.05 % (typical) / 0.1 % + 1 mΩ (guaranteed)

### Power supply

Input voltage	100 V <sub>AC</sub> ... 240 V <sub>AC</sub>
Permissible input voltage	85 V <sub>AC</sub> ... 264 V <sub>AC</sub>
Frequency	50 / 60 Hz
Permissible frequency	45 Hz ... 65 Hz
Input power	500 VA
Connection	Standard AC Socket IEC 60320

### Output

Output voltage	0 ... 120 V
Output current	0 ... 5 A <sub>eff</sub> (15 A <sub>peak</sub> )
Output power	0 ... 400 VA <sub>eff</sub> (1500 VA <sub>peak</sub> )

### Mechanical data

Size (W × H × D)	360 × 285 × 145 mm / 9.2 × 7.2 × 3.7 in
Weight	8 kg / 17.4 lbs (without accessories)

### Environmental conditions

Operating temperature	-10 °C ... +50 °C / 14 °F ... 122 °F
Storage temperature	-25 °C ... +70 °C / -13 °F ... 158 °F
Humidity	Relative humidity 5 % ... 95 % not condensing

### Certificates from independent test institutes

KEMA Test Report
PTB Test Report
Wuhan HV Research Test Report

### System requirements

Operating system	<b>Windows 11™ 64 bit</b>
	Windows 10™ 64 bit

## CT SB2

Input Current	0.2 A
Dimensions (W x H x D)	284 x 220 x 68 mm / 11.2 x 8.7 x 2.7 in
Weight	5.7 lbs / 2.6 kg



## CPOL3

RMS measuring range	1 mV <sub>RMS</sub> ... 1000 V <sub>RMS</sub>
Evaluated signal form	Sawtooth signal > 100 μV <sub>RMS</sub>
Nominal frequency	52.6 Hz
Input impedance	~ 1.8 MΩ (Standard), ~ 3kΩ (LoZ Mode)
Batteries	2 x 1.5 V Mignon AA LR6 FR6 R6 HR6
Dimensions (W x H x D)	68 x 33 x 206 mm / 2.7 x 1.3 x 8.2 in
Weight	245 g (8.6 oz)



# Firmware Packages and Upgrades

		Basic	Standard	Advanced	IEEE Protection
<b>In brief</b>	Measures ratio, composite error, excitation and knee point, winding resistance	■			
	Measures and assesses CTs with accuracy classes $\geq 0.3$ according to IEC and IEEE standards		■		
	Expands standard package to accuracy classes $\geq 0.1$ and additional assessment standards			■	
	Measures protection CTs according to IEEE C57.13 (does not support metering CTs)				■
<b>Firmware Features</b>	CT secondary wiring phase and polarity measurements	■	■	■	■
	Composite error measurements for nominal current	■	■	■	■
	Ratio error and phase displacement measurement for no load and rated load	■	■	■	■
	Measurement of excitation characteristics (voltage/current)				
	> Knee point voltage from 1 V up to 4 kV	■	■	■	■
	> Knee point voltage from 0.1 V up to 40 kV	–	–	■	–
	> Automated calculation of knee points according to IEC and IEEE	■	■	■	■
	> Comparison of excitation curve to a reference curve	–	■	■	■
	CT winding resistance measurement (primary and secondary)	■	■	■	■
	CT accuracy measurements (ratio 1...25000) (ratio error and phase displacement depending on burden and current)				
	> IEC 61869 / 60044, or IEEE C57.13 classes $\geq 0.3$	–	■	■	–
	> IEC 61869 / 60044, or IEEE C57.13 classes $\geq 0.1$	–	–	■	–
	> Customized standards or local / national standards	–	–	■	–
	Automatic assessment of CT performance according to the selected standard	–	■ <sup>1</sup>	■	■
	Customization of assessment rules (for example implementation of national standards)	–	–	■	–
	Composite error measurement for overcurrent conditions (ALF/ALFi, FS/FSi for IEC and $V_b$ for IEEE)	–	■	■	■
	Determination of ALF and FS for IEC or $V_b$ for IEEE	–	■	■	■
	Secondary burden measurement	■	■	■	■
	„Nameplate guesser“ function for CTs with unknown data	–	■	■	■
	Simulation of measured data	–	–	■	■
	Measurement of transient behavior of TPS, TPX, TPY and TPZ type CTs	–	–	■	–
	Determination of the transient dimensioning factor (Ktd)	–	–	■	–
	Considering Duty Cycles C-O / C-O-C-O, for example auto-reclosure system	–	–	■	–
Automatic demagnetization of the CT after the test	■	■	■	■	
Remote control with CT Analyzer Suite software	■	■	■	■	
Flexible manual current and voltage source (QuickTest)	–	■	■	■	
Testing of CTs for line frequencies of 50 Hz	■	■	■	–	
Testing of CTs for line frequencies of 60 Hz	■	■	■	■	
CT SB2 (switch box) for measurements of CTs with up to 6 taps, including accessories	□	□	□	■	
CPOL3 for verifying the correct polarity of the secondary wiring along all connection points	□	□	□	□	
RemAlyzer software for measuring the residual magnetism in CTs	□	□	□	□	
<b>Firmware Upgrades</b>	Basic -> Standard	Upgrades Basic to Standard Package			P0006569
	Basic -> Advanced	Upgrades Basic to Advanced Package			P0006570
	Standard -> Advanced	Upgrades Standard to Advanced Package			P0006566
	IEEE Protection -> Advanced	Upgrades IEEE Protection to Advanced Package			P0006567

<sup>1</sup> IEC 61869-6 not supported ■ included □ optional – not included

# Packages, accessories and services

## Firmware packages including accessories

## Item number

<b>Basic</b>	For measurements such as ratio check, composite error, excitation and knee point, winding resistance	P0000853
<b>Standard</b>	For measurements and automatic assessment on CTs with accuracy classes $\geq 0.3$ according to IEC and IEEE standards	P0000846
<b>Advanced</b>	Expands standard package functionality to accuracy classes $\geq 0.1$ and additional assessment standards	P0000848



<b>IEEE Protection</b>	For protection CTs according to IEEE C57.13 (does not support metering CTs)	P0000847
------------------------	---	----------




PC software features	Free Standard Software	PC Software Upgrade Option (P0000413)
Guided test execution via PC	■	■
Detailed connection diagrams	■	■
Test reports	■	■
Convenient summary of test results	■	■
Advanced test reports (e.g. combination of multiple tests)	—	■
Report template design editor	—	■
Multi-test view	—	■
Results simulation without the need to connect the CT Analyzer	—	■

■ included □ optional — not included

Please find detailed ordering information and package descriptions on [www.omicronenergy.com](http://www.omicronenergy.com)

## Accessories

## Item number

CT SB2 including accessories		Switch box for measurements on CTs with up to 6 taps	P0006328
Training CT		Class 0.5 CT for training purposes, FS 5, ratio 300:5	E0556200
Calibration CT		High-precision CT (class 0.02) for calibration purposes, ratios 2000:1 / 2000:5	P0005223
Winding		Pluggable 23 turns winding for measurements on magnetic cores without secondary winding	B0593901
CPOL3		Polarity and wiring checker for CTs' secondary wiring	P0009398
RemAnalyzer		Determines the residual magnetism in CTs (additional software license)	P0006790
Transport case with wheels		Suitable for unattended shipping	B0553701
Multi-functional transport case		Suitable for unattended shipping. Convertible into a workbench.	B1636100

## Calibration services

## Item number

Recalibration of high-precision CT	Recalibration of high-precision CT according to ISO / IEC 17025 (recommended every 1-2 years)	P0006035
Calibration of new CT Analyzer	Calibration of new CT Analyzer devices according to ISO / IEC17025 (certificates included)	P0006017
Recalibration of CT Analyzer in service	Recalibration of CT Analyzer according to ISO / IEC 17025 (includes certificates, recommended every 1-2 years)	P0006031

We create customer value through ...

## Quality


We always want you to be able to rely on our testing solutions. This is why our products have been developed with experience, passion and care and are continually setting ground-breaking standards in our industry sector.



You can rely on the highest safety and security standards

Superior reliability with up to

72



hours burn-in tests before delivery

100%

routine testing for all test set components




ISO 9001  
TÜV & EMAS  
ISO 14001  
OHSAS 18001



Compliance with international standards

# Innovation

Thinking and acting innovatively is something that's deeply rooted in our genes. Our comprehensive product care concept also guarantees that your investment will pay off in the long run – e.g. with free software updates.

More than  
**200**   
developers keep  
our solutions up-to-date

 I need...   
... a product portfolio  
tailored to my needs

More than  
**15%**   
of our annual sales is  
reinvested in research and  
development

Save up to  
**70%**    
testing time through  
templates, and automation


We create customer value through ...

## Support


When rapid assistance is required, we're always right at your side. Our highly-qualified technicians are always reachable. Furthermore, we help you minimize downtimes by lending you testing equipment from one of our service centers.




Professional technical support  
at any time



Loaner devices help to  
reduce downtime



Cost-effective and straight-  
forward repair and calibration



offices worldwide for local  
contact and support

## Knowledge

We maintain a continuous dialogue with users and experts. Customers can benefit from our expertise with free access to application notes and professional articles. Additionally, the OMICRON Academy offers a wide spectrum of training courses and webinars.



Frequently OMICRON hosted user meetings, seminars and conferences


More than

**300** 

Academy and numerous hands-on trainings per year



to thousands of technical papers and application notes



Extensive expertise in consulting, testing and diagnostics

OMICRON is an international company that works passionately on ideas for making electric power systems safe and reliable. Our pioneering solutions are designed to meet our industry's current and future challenges. We always go the extra mile to empower our customers: we react to their needs, provide extraordinary local support, and share our expertise.

Within the OMICRON group, we research and develop innovative technologies for all fields in electric power systems. When it comes to electrical testing for medium- and high-voltage equipment, protection testing, digital substation testing solutions, and cybersecurity solutions, customers all over the world trust in the accuracy, speed, and quality of our user-friendly solutions.

Founded in 1984, OMICRON draws on their decades of profound expertise in the field of electric power engineering. A dedicated team of more than 900 employees provides solutions with 24/7 support at 25 locations worldwide and serves customers in more than 160 countries.

The following publications provide further information on the solutions described in this brochure:

Additional literature:



For more information, additional literature, and detailed contact information of our worldwide offices please visit our website.